

## RT22 Hand transmitter

The RT22 hand transmitter can control 24 Easywave receivers.

The RT22 has four levels (I to IV), each with six individually coded radio channels:

- 5 channels have the ON/OFF function
- 1 channel has the UP/STOP/DOWN function.

The multi-channel transmitter is best used when multiple Easywave receivers need to be controlled from a single hand transmitter.

Its solid housing and large buttons, which are easy to operate, make the RT22 suitable for industrial applications.



RT22E5022-01-23K

### Technical specifications

Coding	factory coding with Easywave telegram
Frequency	868.30 MHz
Channels	24
Range	typically 150 m in good free-field conditions
Power supply	2x 3V batteries, CR2032
Operating indicator	LEDs
Operation	See operating manual
Function	depends on the receiver (see models)
Operating temperature	-20 °C to +60 °C
Dimensions	60 x 150 x 22 mm (without wall holder)
Weight	100 g (including batteries)
Color	anthracite gray similar to RAL 7016

### Scope of delivery

- Hand transmitter including batteries
- Operating manual

### Accessories (optional)

RT22-ACC-01-23P	Wall holder, anthracite gray
-----------------	------------------------------



RT22-ACC-01-23P

### Models

Product numbers	Description	Function
RT22E5022-01-23K	Hand transmitter 24-channel, anthracite gray	20x ON/OFF 4x UP/STOP/DOWN