

RT42 | RT43 Hand transmitter PULSE

The RT42 and RT43 are radio transmitters designed for universal use. They can be used together with any Easywave receiver and in any of the operating modes available.

The RT43 is the standard version with a plastic bracket, whereas the RT42, the premium version, is equipped with a chrome-plated metal bracket.

The transmitter can be used to control roller shutters for example or, more generally, to switch electrical devices on or off.

An easily visible LED lights up when the battery needs to be changed.



RT43E5004-01-21K

RT42E5004-01-21K

Technical specifications

Coding	Factory coding with Easywave telegram
Frequency	868.30 MHz
Channels	4
Range	typically 150 m in good free-field conditions
Power supply	1x 3V battery, CR2032
Operating indicator	LED
Operation	transmission lasts as long as the button is pressed (maximum 36 seconds)
Operating temperature	-20 °C to +60 °C
Dimensions (W/L/H)	37/61,5/10,7 mm
Weight	RT42: 30 g (including battery) RT43: 18 g (including battery)
Color	black similar RAL 9005

Scope of delivery

- Hand transmitter including battery
- Key protection
- Operating manual

Accessories (optional)

RT42-ACC-01-21U	key protection for RT42/RT43 black similar to RAL9005
-----------------	--



Models

Product numbers	Description
RT42E5004-01-21K	Hand transmitter, Easywave, 4x PULSE, metal bracket, black
RT43E5004-01-21K	Hand transmitter, Easywave, 4x PULSE, plastic bracket, black